

Beaver dam analogue configurations influence stream and riparian water table dynamics of a degraded spring-fed creek in the Canadian Rockies

Journal:	<i>River Research and Applications</i>
Manuscript ID	RRA-20-0198.R1
Wiley - Manuscript type:	Research Article
Date Submitted by the Author:	21-Sep-2020
Complete List of Authors:	Munir, Tariq; University of Saskatchewan, Geography and Planning Westbrook, Cherie; University of Saskatchewan, Centre for Hydrology;
Keywords:	beaver, beaver dam analogue, BDA design, riparian, stream, Canadian Rockies, Water table

SCHOLARONE™
Manuscripts

1 Beaver dam analogue configurations influence stream and riparian water table 2 dynamics of a degraded spring-fed creek in the Canadian Rockies

3
4
5
6
7
8 Tariq M. Munir^{1*} and Cherie J. Westbrook¹

9
10 ¹Department of Geography and Planning, Centre for Hydrology, University of Saskatchewan, Saskatoon,
11 SK, CANADA S7N 5C8

12
13 *corresponding author: tariq.munir@usask.ca; +1 (403) 971-5693

14 15 16 17 ABSTRACT

18
19 Beaver dam analogues (BDAs) are intended to simulate natural beaver dam ecohydrological functions
20 including modifying stream hydrology and enhancing stream-riparian hydrological connectivity. River
21 restoration practitioners are proactively deploying BDAs in thousands of degraded streams. How various
22 BDAs or their configurations impact stream hydrology and the riparian water table remains poorly
23 understood. We investigated three types of BDA configurations (single, double and triple) in a spring-fed
24 Canadian Rocky Mountain stream over three study seasons (April-October; 2017-2019). All three BDA
25 configurations significantly elevated the upstream stage. The deepest pools occurred upstream of the
26 triple-configuration BDAs (0.46 m) and the shallowest pools occurred upstream of the single-
27 configuration (0.36 m). Further, the single-BDA configuration lowered stream stage and flow peaks
28 below it but raised low flows. The double-BDA configuration modulated flow peaks but had little
29 influence on low flows. Unexpectedly, higher flow peaks and low flows were recorded below the triple-
30 BDA configuration, owing to groundwater seep. Similar to the natural beaver dam function, we observed
31 an immediate water table rise in the riparian area after installation of the BDAs. The water table rise was
32 greatest 2 m from the stream (0.14 m) and diminished with increasing lateral distance from the stream.
33 Also noted was a reversal in the direction of flow between the stream and riparian area after BDA
34 installation. Future research should further explore the dynamics of stream-riparian hydrological
35 connections under various BDA configurations and spacings, with the goal of identifying best practices
36 for simulating the ecohydrological functions of natural beaver dams.
37
38
39
40
41
42
43

44 45 KEYWORDS

46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

99 100 RUNNING HEAD

101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

36 1 INTRODUCTION

37 A formidable challenge in restoring degraded streams is re-establishing stream-riparian area
38 connectivity. Streams in drought-prone areas often become incised and subsequently disconnected
39 from riparian areas after beavers (*Castor canadensis*) are removed (Pollock et al., 2014). Anecdotal and
40 modelling evidences suggest that the return of beavers improves the two-way flow of water and
41 sediments between streams and riparian areas (Stout, Majerova & Neilson, 2017), and regulates the
42 processes critical in restoring wetland conditions (Fairfax & Small, 2018; Pilliod et al., 2018). However,
43 there may be asymmetry in the effects of key species removal and restoration owing to unexpected
44 feedbacks that reinforce the effects of the species loss (Marshall, Hobbs & Cooper, 2013). While it is
45 ultimately up to the beavers whether they want to recolonize degraded streams and associated riparian
46 areas (Dewas et al., 2012), there is tremendous potential for restoring these streams using alternate,
47 process-based restoration strategies such as restoring beavers to streams (Johnson et al., 2020).

48 Many stream restoration practitioners are already partnering with beaver. This is because of the
49 growing recognition of how beavers engineer channel spanning dams and their effects on river corridors
50 (Harvey & Gooseff, 2015). Beaver dams increase hyporheic exchange and ponding (Janzen & Westbrook,
51 2011), decrease stream velocity (e.g., Stout et al., 2017) and increase aggradation (e.g., Butler &
52 Malanson, 2005; Pollock, Beechie & Jordan, 2007). Additionally, beaver dams develop backwater
53 impoundments (Stout et al., 2017) that indirectly control the health and biodiversity of riparian areas
54 and ensure relatively consistent streamflow year-round (Pollock et al., 2014; Puttock et al., 2017;
55 Westbrook, Cooper & Baker, 2011). Multiple beaver dams in sequence may have stronger control over
56 the ecohydrologic and geomorphic processes regulating streams and riparian areas than a single dam
57 (Polvi & Wohl, 2012). As a result, beavers are keystone species progressively acknowledged for exerting
58 disproportionately large hydrogeomorphic and ecohydrological effects on the watershed-scale
59 environment compared with their abundance (Puttock et al., 2017; Rosell, Bozser, Collen & Parker,
60 2005). The current influence of beavers on mountain streams is however greatly reduced compared to
61 that prior to the European fur trade (Persico & Meyer, 2013).

62 In the absence of natural beaver recolonization, dam structures intended to mimic the form and
63 function of beaver dams, called beaver dam analogues (BDAs) are used for restoring degraded streams.
64 BDAs are low tech and inexpensive, constructed to be permeable instream structures made up of
65 branches, mud and rock (Pilliod et al., 2018; Pollock et al., 2018; Scamardo & Wohl, 2020). There are
66 three generic BDA designs that differ in structure, materials and desired outcomes (Pollock, Wheaton,
67 Bouwes & Jordan, 2011; Pollock et al., 2018), sometimes referred to as standard BDAs (Scamardo &
68 Wohl, 2020). The types are, 1) starter dams – vertical posts with willow woven between the posts
69 (wicker weave) and fill material (e.g., cobble, vegetation, and mud) placed upstream, 2) post lines and
70 wicker weave – just post lines with wicker weaves, which are highly permeable, and 3) reinforced
71 existing or abandoned natural beaver dams which involves simply reinforce existing or abandoned
72 natural structures using vertical posts. Recently, Scamardo and Wohl (2020) installed two types of BDA:
73 1) traditional post and willow BDAs (Pollock et al., 2018) made up of few large wood posts (diameter
74 >0.10 m) inserted in the stream bed with thinner branches woven between posts and staked on the

75 downstream end of BDA, and 2) non-traditional wood-jam BDAs built of large logs partially buried in the
76 banks across the bed and perpendicular to flow. These BDAs were also individually dispersed structures.

77 BDAs have been deployed in thousands of degraded streams (Lautz et al., 2019). Similar to natural
78 beaver dams, BDAs aggrade the channel and stream bed (Scamardo & Wohl, 2020) and thus raise water
79 tables in the riparian area (Briggs, Lautz, Hare & González-Pinzón, 2013; Feiner & Lowry, 2015; Karran,
80 Westbrook & Bedard-Haughn, 2018). A higher riparian water table helps to support healthy riparian
81 plant communities (Dittbrenner et al., 2018; Silverman et al., 2019; Westbrook, Cooper & Baker, 2006)
82 while slowing of stream water helps moderate stream temperatures (Majerova et al., 2015; Weber et
83 al., 2017). BDAs are not intended to be long-term infrastructures. Rather, they are intended to be short-
84 lived and initiate positive ecological and hydrogeomorphic feedback loops such that beaver can
85 reoccupy the site at some future date (Pollock et al., 2018).

86 BDAs are deployed in a variety of configurations, ranging from one individual structure to multiple
87 structures installed in sequence. For example, Orr et al. (2020) used five individual structures dispersed
88 over a small scale restoration reach of 2.25 km, and Bouwes et al. (2016) installed 100+ BDAs on the
89 large scale restoration of Bridge Creek, in Oregon, USA. The BDA configuration is flexible and should
90 depend on the hydrogeomorphic and ecologic settings (Pilliod et al., 2018) and also on the restoration
91 project goal(s) (Pollock et al., 2011). Commonly, multiple BDAs are installed in sequence (Charnley,
92 2018; Pilliod et al., 2018), since short sequences of natural beaver dams can have an exaggerated impact
93 on surface water storage and flow attenuation (Stout et al., 2017). Further, installing multiple BDAs
94 should add redundancy to the system, which may be useful in ensuring some BDAs persist following
95 larger flow events. However, the efficacy of different BDA configurations, which would be useful to
96 restoration practitioners and regulators in making informed decisions on their use, has not been studied
97 in a scientific context (Lautz et al., 2019; Pilliod et al., 2018). Thus, the goals of our study were to
98 compare the effects of different BDA configurations on stream hydrology, and also test the efficacy of a
99 single-BDA configuration in raising the riparian groundwater table. We hypothesized that the stream
100 stage and stream discharge would be greater affected by having multiple BDAs in sequence. We also
101 expected an increase in and stabilization of the riparian groundwater table following the installation of a
102 single BDA.

103

104 2 MATERIALS AND METHODS

105 2.1 Study Area

106 The study was conducted in Ann & Sandy Cross Conservation Area (ASCCA), a 19.4 km² natural area in
107 the rolling foothills of the Canadian Rocky Mountains, located 32 km southwest of downtown Calgary,
108 near the town of Priddis in Alberta. Prominent hydrogeology of the region includes Paskapoo Formation,
109 which is an extensive Paleocene-aged fluvial mudstone and sandstone complex and supports more
110 groundwater wells than any other aquifer system in the Canadian Prairies (Grasby et al., 2008). There
111 are a number of springs in ASCCA and most of them flow year-round. Pine Creek is a spring-fed

1
2
3 112 mountain stream that flows west-east in ASCCA. It is a tributary of the Bow River which flows into the
4 113 South Saskatchewan River. Dominant vegetation ecology of ASCCA consists of an overstory of balsam
5 114 poplar (*Populus balsamifera*), trembling aspen (*Populus tremuloides*) and white spruce (*Picea glauca*)
6 115 with an understory of shrubs including prickly rose (*Rosa acicularis*) and snowberry (*Symphoricarpos*
7 116 *albus*) mixed with tall anemone (*Anemone virginiana* var. *cylindroidea*), smooth brome (*Bromus inermis*
8 117 ssp. *Inermis*), bluejoint (*Calamagrostis canadensis*), northern reed (*Calamagrostis stricata* spp.
9 118 *Inexpansa*) and small bottle sedge (*Carex utriculata*) graminoids. Thirty-year (1981-2010) mean seasonal
10 119 (May-October) temperature and precipitation normals in the region are 12.2 °C and 63.5 mm,
11 120 respectively.

12 121 Historically, ASCCA's topography, vegetation cover and hydromorphology made favourable beaver
13 122 habitat; remnant beaver dams in Pine Creek watershed are still visible. Beavers were lost from the
14 123 conservation area by the early 1990s as a result of illegal trapping (G. Shyba, pers. comm.). They are
15 124 unable to naturally re-disperse into the site as the creek downstream is fenced down to its bed. In an
16 125 attempt to re-establish this keystone wildlife species in ASCCA, the Alberta Institute for Wildlife
17 126 Conservation reintroduced a pair of beavers on May 18, 2018 (White, 2016), but not to the study reach.
18 127 In the absence of beaver, Pine Creek has degraded. The stream is incised, and the riparian vegetation
19 128 coverage is severely reduced, which makes the site poor beaver habitat.

20 129 2.2 Methods

21 130 We studied a 1072-m long reach of the north arm of Pine Creek. The reach has an average stream width
22 131 of 0.63 m, W-E and N-W slopes of 1.22% and 0.21%, respectively, and an approximate elevation of 1150
23 132 m above sea level. A total of six BDA structures were installed between August 3 and 9, 2018 along the
24 133 study reach. The BDAs were installed as single (BDA-6), double (BDA-2, BDA-1) and triple (BDA-5, BDA-4,
25 134 and BDA-3) configurations following Pollock et al. (2011). Each BDA was constructed from co-linear
26 135 wooden posts (1.0 m long and ~0.07 m in diameter) driven into the stream bed by hand in one line.
27 136 Aspen branches harvested onsite were interwoven between the posts and the structures were further
28 137 reinforced with mud from the stream bed to achieve a consistent stream stage at each (~0.60 m). BDA
29 138 width ranged from 0.77 to 0.49 m, depending on the local creek width.

30 139 Stream stage was monitored at four locations along the study reach in the thalweg, starting in May
31 140 2018. Stream gauges (SG (levellogger junior 3001, Solinst, Ontario, Canada); SG-4 – SG-1) were installed
32 141 upstream of the BDAs, and downstream of each BDA configuration (Fig. 1). Stage was converted to
33 142 discharge with a rating curve. An OTT MF Pro – Water Flow Meter (OTT Hydromet, Loveland, CO, USA)
34 143 was used to measure streamflow and develop the rating curve. For May-October of 2018-2019, the
35 144 stream stage was observed at each gauge at 15-min intervals. The barometric pressure was concurrently
36 145 measured every 15-min with a barologger (Solinst) inserted into a dry standpipe located in the riparian
37 146 area; data were used to correct levellogger observations. Rainfall observations were obtained from the
38 147 Alberta Environment and Parks rain gauge at Priddis (station ID 3033505), located 7.5 km west of the
39 148 study reach at 1371 m elevation.

1
2
3 149 We monitored BDA pond level immediately upstream of each BDA (PG-6 to PG-1) between April 2019-
4 150 August 2019. Levels were measured by housing an automatic levellogger (levellogger junior 3001, Solinst,
5 151 Georgetown, Ontario, Canada) in a perforated PVC pipe (length = 1.0 m; diameter = 0.035 m) inserted
6 152 0.30 m into the streambed. The levelloggers monitored temperature-compensated levels at 15-min
7 153 intervals, corrected for barometric pressure as described above, and averaged over the BDA
8 154 configurations. Daily means were used for plotting pond water levels and conducting statistical analysis
9 155 in all cases.

10
11
12
13 156 Three groundwater (GW) wells (1, 2, 3) were installed in June 2017 in the riparian area to the south of
14 157 BDA-6, at distances of ~2, 7, and 13 m from the stream. The wells were built by inserting a 1.75 m long
15 158 PVC pipe (diameter = 0.035 m; bottom 1.25 m perforated and wrapped with 1.5 μ m polypropylene mesh
16 159 net) to a depth of ~1.25 m following Westbrook et al. (2006). The pipes were outfitted with automatic
17 160 levelloggers (Levellogger Junior 3001, Solinst, Georgetown, Ontario, Canada). Water levels in the GW
18 161 wells were observed during the study period (frost-free periods of 2017-2019), except the levels from
19 162 well-2 could not be retrieved for 2019 due to instrument malfunction. Levelloggers recorded
20 163 temperature-compensated water levels continuously at 15-min intervals throughout the three ground
21 164 frost-free seasons (April/May-October) of 2017-2019, and corrected for barometric pressure as
22 165 described earlier.

23 166 2.3 Data analysis

24
25
26
27 167 SPSS 26.0 package (SPSS, Chicago, IL, USA) was used for statistical analyses (Landau & Everitt, 2004).
28 168 Separate linear mixed-effects models (LMEM) used the entire dataset (Munir & Westbrook, 2020) to
29 169 predict the fluctuations in stream stage, streamflow, BDA pond water level and riparian GW table in
30 170 response to the fixed effects of BDA-configuration (single, triple and double), rainfall, BDA pond water
31 171 level, stream stage and streamflow as applicable. A random variable of BDA configuration (distance from
32 172 the top of the reach) was used to cover the effects of upstream/downstream configurations on the
33 173 predictor and outcome variables. For GW table as a response variable, both the depth to GW table and
34 174 absolute elevation values were separately tested and found to have equivalent significance; therefore,
35 175 to be consistent with other analyses, the depth to GW table was used for final analysis. Any significant
36 176 interactions between rainfall and other predictors (BDA pond level, stream stage, streamflow) were not
37 177 only the result of collinearity, for example, the interaction of rainfall with BDA configurations had
38 178 different significance (F or t and p values) for stream stage and streamflow. A compound symmetry
39 179 covariance structure was used in all LMEM applications. Daily mean stage and discharge values were
40 180 obtained by subtracting daily downstream values from corresponding upstream values; these data were
41 181 used in the model. Before analyses, all data were tested for normality and homogeneity of variance
42 182 using the Kolmogorov-Smirnov test and Levene's test, respectively. Regressions and 1:1 fit (s) were also
43 183 performed where useful to validate the models developed. A significance level of 95% ($p < 0.05$) and/or
44 184 LogWorth ($-\log_{10}(p)$) ($p < 0.01$) was used. The goodness of fit was reported as R^2 value.

45 185

46 186 3 RESULTS

1
2
3 187 Total May-October rainfall measured at the nearby rain gauge was lower in 2017 (160 mm) than in 2018
4 188 (277 mm) or 2019 (317 mm). Mean seasonal air temperature was higher in 2017 (12.3 °C) than 2018
5 189 (11.7 °C) or 2019 (11.5 °C). A large rainfall event of 57.5 mm occurred on June 21, 2019. However, the
6 190 site received 135.1 mm of rain between 21 June and 7 July 2019, with at least 0.5 mm of rain falling on
7 191 15 of those 20 days. Smaller rainfall events (10-30 mm) over the study period also significantly
8 192 influenced the surface and shallow floodplain hydrology of this study creek.

11 12 193 3.1 BDA pond water level

13
14 194 BDAs were successfully constructed in early August 2018 along Pine Creek to achieve a ponded depth of
15 195 approximately 0.50 m at each. The BDAs failed twice during the 13-month experiment – once over
16 196 winter and again following intense summer rainstorms – via undercutting. All BDAs were repaired at the
17 197 end of April 2019 following ice-off, but were not repaired following the summer rainstorms. Automated
18 198 BDA pond water levels measured on the day following BDA installations (August 10, 2018) were
19 199 significantly higher than those recorded on the last day of their final failure (August 5, 2019; Fig. 2A;
20 200 paired t-test; $p < 0.001$). During the BDA deployment period, most of the structures were fatally damaged
21 201 by the extreme rainfall event occurring on June 21, 2019, and started fully draining after the very rain
22 202 period ending July 7, 2019 (Fig. 2B, 2C). Among the triple configuration BDAs, the middle BDA (4)
23 203 continued to hold more water than the upstream BDA (5) by 12%. On average, the triple configuration
24 204 series held 26% and 6% more water than the single and double configurations, respectively. There was
25 205 greater water storage above the triple configuration than the single and double configurations for a
26 206 total of 87 days and 61 days, respectively.

27 207 Overall, BDA configuration was a significant predictor of pond water level. The pond water level
28 208 increased immediately upstream of all BDA configurations ($p < 0.001$; LogWorth = 12.31; Table 1, Fig. 2A).
29 209 However, the mean water levels (\pm SE) at the triple (0.47 ± 0.00 m) and double (0.44 ± 0.00 m)
30 210 configurations were higher than that at the single (0.37 ± 0.01 m) configuration (Fig. 2C). Rainfall was
31 211 also a significant predictor of BDA pond water level, and all three BDA configurations showed increased
32 212 ponding in response to rainfall/events. Increases in pond water levels upstream of BDAs 6, 5 and 4 in
33 213 response to the largest rainstorms were greater than those at upstream of BDAs 3, 2 and 1 (Fig. 2B).

34 214 3.2 Stream stage and flow

35 215 Stream stage and discharge were lower at the gauging stations downstream of BDA installations than
36 216 upstream of them (Fig. 3A, 3C, 4A, 4C). Similar stage and discharge trends 120 m downstream of double
37 217 configuration at SG-1 and the same distance upstream of single configuration at SG-4 were also
38 218 observed (Fig. 3D, 4D). The one exception was the triple configuration, where the downstream stage at
39 219 SG-2 was higher than that at the upstream stage at SG-3 (Fig. 3B, 4B). Single configuration BDA (6)
40 220 mitigated stormflow by lowering the downstream stage and increasing baseflow compared to the
41 221 double configuration that simply reduced both downstream stage and discharge.

42 222 Paired t-tests (pre- vs post-BDA installation) were significant, which indicated that all BDA configurations
43 223 resulted in elevated stream stage while only single-configuration (BDA-6) impacted stormflow (Table 2).

224 To factor out changes in stream hydromorphology owing to BDA configuration, rainfall, and pond water
 225 level predictors, LMEMs were performed. Overall, both the stream stage and flow before BDA
 226 installations were significantly different from those recorded after the BDA installation. Further, the
 227 triple- and double-configurations had more influence on stream stage and flow than the single-
 228 configuration (BDA-6). We present the stream stage and flow prediction expressions generated by the
 229 statistical models as:

$$\begin{aligned}
 \text{Stream stage} &= 0.0025 + 0.0009 \text{ (single-config.) or } 0.0107 \text{ (double-config.) or } 0.0098 \text{ (triple-config.)} + \\
 & 0.0069 \times \text{BDA pond level} \\
 &= 0.0025 + 0.42 \text{ (BDA pond level)} \times 0.1144 \text{ (single-config.) or } 0.0369 \text{ (double-config.) or } - \\
 & 0.1513 \text{ (triple-config.)} + 0.0002 \times \text{rainfall} \\
 &= 0.0025 + 2.28 \text{ (rainfall)} \times -0.0001 \text{ (single-config.) or } -0.0002 \text{ (double-config.) or } 0.0003 \\
 & \text{(triple-config.)} + 0.42 \text{ (BDA pond level)} \times (2.28 \text{ (rainfall)} \times 0.0008) \\
 \text{Streamflow} &= 3.5277 + 0.2422 \text{ (single-config.) or } 9.4017 \text{ (double-config.) or } 9.1595 \text{ (triple-config.)} - \\
 & 4.7780 \times \text{BDA pond level} \\
 &= 3.5277 + 0.42 \text{ (BDA pond level)} \times 23.79 \text{ (single-config.) or } 49.40 \text{ (double-config.) or } - \\
 & 73.19 \text{ (triple-config.)} + 0.1304 \times \text{rainfall} \\
 &= 3.5277 + 2.28 \text{ (rainfall)} \times 0.1890 \text{ (single-config.) or } 0.2310 \text{ (double-config.) or } -0.4200 \\
 & \text{(triple-config.)} + 0.42 \text{ (BDA pond level)} \times (2.28 \text{ (rainfall)} \times 0.2497)
 \end{aligned}$$

242 Rainfall and BDA pond water level were not significant predictors for stream stage and flow; however,
 243 there was a two-way interaction between rainfall and BDA configuration, which revealed that there
 244 were significant increases in streamflow and stage at the upstream of single and double configurations
 245 (at SG-4 and SG-2, respectively). We also found a three-way interaction between rainfall, BDA
 246 configuration and BDA pond water level, which demonstrated the incremental stage and flow upstreams
 247 of these configurations. Individually, the rainfall, which was a non-significant predictor in the model
 248 (LMEM: $p=0.296, 0.177$), was collinear with stream stage and flow (one-way ANOVA: $p<0.001, n = 169$).

249 The discharge responses to rainfall events varied across upstream and downstream of BDA-
 250 configurations. Relationships between above- and below-BDA configuration rainfalls and discharge data
 251 for summary metrics of peak event discharge and total event discharge are shown in Fig. 5A, 5B, 5C, 5D,
 252 and 5E, 5F, 5G, and 5H, respectively. Below single- and double-configurations, both the peak event and
 253 total storm event discharges showed more attenuating responses to rainfall events compared to those
 254 at above these structures. The one exception was the triple-configuration where upstream SG-3
 255 measured lower flow compared to the downstream SG-2. Deeper analyses of discharge data revealed
 256 that downstream of BDA sequences, the average peak flows at SG-3 (4.5 l/s) and SG-1 (16.2 l/s) were
 257 smaller than corresponding upstream of BDA measurements (at SG-4 by 39% ($p<0.018, n = 19$) and SG-2
 258 by 63% ($p<0.001, n = 19$)). Simultaneously, downstream of BDA sequences the average total event

1
2
3 259 discharge at SG-3 (74.5 m³) and SG-1 (57.3 m³) were smaller than corresponding upstream of BDA
4 260 sequences at SG-4 by 28% ($p < 0.019$, $n = 19$) and SG-2 by 88% ($p < 0.001$, $n = 19$). For the triple-
5 261 configuration, the downstream (SG-2) average peak flow and total event discharge (34.7 l/s and 488.9
6 262 m³, respectively) were higher than those measured upstream (SG-3) by 670% and 554%, respectively
7 263 ($p < 0.001$, $n = 19$).

10 264 3.3 Riparian groundwater hydrology

11
12
13 265 Stream hydrology was found to relate to the riparian GW table post-restoration, as reflected by
14 266 uninterrupted and stable links of BDA ponding and upstream stage with GW levels at monitoring wells
15 267 (Table 3; Fig. 6, 7). Mean GW levels at monitoring wells 1, 2 and 3 were -0.46, -0.40 and -0.68 m during
16 268 2017, and -0.39, -0.66 and -0.83 m during 2018 study years (negative values indicate WT is
17 269 belowground). After the BDAs were installed, the mean GW levels in 2019 were -0.32 m at well-1 and -
18 270 0.65 m at well-3. BDA-6 was built on 3 Aug 2018. Two days later, GW levels had risen by 0.53 m at well-
19 271 1, 0.30 m at well-2 and 0.05 m at well-3, which showed that the effects of the BDA decreased with
20 272 increasing distance from the stream ($p < 0.05$; $n = 308$). Detailed pre- vs post-BDA installation differences
21 273 in riparian GW levels and elevations driven by a single-configuration BDA and augmented by ponding
22 274 and rain events are shown in Fig. 6A and 6B. One of the largest rain events occurring on 21 June 2019
23 275 caused the GW table to rise from 1127.15 and 1126.99 masl at wells 1 and 3 (recorded on 20 June) to
24 276 1127.34 and 1127.30 masl, respectively. Pre-BDA installation, hydraulic gradient (Fig. 6B) indicated flow
25 277 from the riparian area to the stream. As soon as BDA-6 was installed there was a flow reversal wherein
26 278 stream water flowed below ground toward the riparian area. The two large rainstorms transiently
27 279 created a flow reversal in the opposite direction. A paired t-test comparing riparian GW levels pre- (9
28 280 Aug 2017-2 Aug 2018) and post-installation (5 Aug 2018-5 Aug 2019) informed significant increases in
29 281 GW levels post-deployment of single-configuration BDA (Table 3; $p < 0.001$; $n = 131$).

30
31
32 282 To find out whether the single-configuration (BDA-6) and associated pond water level, rainfall and
33 283 stream stage were significant predictors for shallow GW hydrology of the riparian area, we conducted a
34 284 LMEM with a random effect of well location (Table 3) to account for hydrological variations possibly
35 285 caused by these variables. We found a significant interaction between BDA pond water level and stream
36 286 stage (SG-4), and significantly elevated GW levels at well-1 and 3 ($p < 0.001$); though, individually,
37 287 ponding increased level at well-1 only ($p < 0.001$), and upstream stage raised water elevation at well-3
38 288 alone ($p < 0.001$). Rainfall was a common significant predictor of GW level at both wells; however, there
39 289 was an interaction of rainfall with ponding, which demonstrated GW elevations at both wells. The LMEM
40 290 results we obtained were also validated by linear regression models for demonstrating how rainfall,
41 291 stream stage and ponding had controls on GW elevations at wells 1 and 3 (Fig. 7A, 7B). Riparian GW
42 292 levels measured at each well were separately plotted against the corresponding predicted values
43 293 generated by the models to construct 1:1 fit in each case (Fig. 7C, 7D).

44 294

45 295

1
2
3 296 5 DISCUSSION
4

5
6 297 Our findings have important implications for those in management who may be considering the
7 298 installation of BDAs. We showed that BDAs modified stream and riparian area hydrology at this site in
8 299 ways consistent with how natural beaver dams modify stream and riparian area hydrology. Having more
9 300 BDAs installed in a sequence generally enhanced their influence on stream hydrology. However, diffuse
10 301 spring inputs to the stream can obscure the hydrologic influence of BDAs.
11
12

13 302 5.1 Surface-water: ponding and elevation
14

15 303 Surface water ponding upstream is one of the well-recognized functions of natural beaver dams and has
16 304 been frequently reported (e.g., Pollock et al., 2014; Puttock et al., 2017; Stout et al., 2017). Rarely
17 305 though is BDA-induced ponding investigated (Bouwes et al., 2016; Orr et al., 2020; Scamardo & Wohl,
18 306 2020). We found that all three BDA configurations created upstream ponds. While all the BDAs were the
19 307 same height, there was a difference in pond depth depending on the type of configuration. The deepest
20 308 ponds were recorded at the immediate upstreams of triple-configuration ($0.46 \pm 0.09\text{m}$) followed by the
21 309 ponding levels at double- ($0.43 \pm 0.10\text{m}$) and single-configurations ($0.36 \pm 0.08\text{m}$). This finding supports
22 310 the notion that a multiple structure BDA configurations can create deeper pools, similar to the function
23 311 of natural beaver dams (Pilliod et al., 2018; Pollock et al., 2018). Of all configurations, the double-
24 312 configuration appeared to modulate the impacts of storm events and sustain consistent depth the most,
25 313 which could be attributed to their lowest position on reach slope. Secondly, rainfall was a key factor
26 314 in raising pond level. BDA configuration and rainfall did not have a meaningful interaction, which is likely
27 315 the result of the low crest BDA design we used which was prone to quickly overtopping by stormflow,
28 316 similar to the observations made by Bouwes et al. (2016). Substantially lowered pond levels at all BDAs
29 317 except BDA-4 were noticed upon complete failure of BDAs at the end of this experiment (August 5,
30 318 2019) compared to elevations recorded soon after their installation (August 5, 2018). Prolonged
31 319 functioning of the middle BDA (4) of the triple-configuration could indicate that the number of dams in a
32 320 sequence matters when it comes to the persistence of the upstream ponding and depth. Where natural
33 321 beaver dams occur in sequence, Westbrook, Ronnquist and Bedard-Haughn (2020) found a lower
34 322 likelihood of all dams in the sequence failing during large rainfall events.
35
36
37
38
39
40
41

42 323 5.2 Stream stage and flow
43

44 324 One of the key reasons why hundreds of BDAs have been installed across first to third-order streams
45 325 during the last two decades in Western North America (see Pilliod et al., 2018; Pollock et al., 2014) is to
46 326 alter stream hydrology. Natural beaver dams are known to reduce hydrograph peaks (Hillman, 1998)
47 327 and elevate baseflows (Westbrook, Cooper & Butler, 2013); only a few studies have reported that BDAs
48 328 performed similarly, for example, Bouwes et al. (2016). We found mixed results of the effectiveness of
49 329 BDA in altering stream hydrology as did Scamardo and Wohl (2020). The single-BDA configuration
50 330 lowered stream stage and flow peaks after rainfall events and raised base stage and low flows. The
51 331 double-BDA configuration, however, modulated peaks but had little influence on base stage and low
52 332 flows. Little or no changes in base stage and flow could be due to the interaction of steeper slope
53 333 (1.22%) of the reach in which the double-BDA configuration was installed or weak hydrological
54
55
56
57
58
59
60

1
2
3 334 connectivity of the stream with the adjacent historical riparian wetland. Unexpectedly, higher peaks and
4 335 base stage/flow were recorded downstream of the triple-configuration than upstream of it following
5 336 rainfall events. Higher stage and flow downstream of the triple-BDA configuration seemed not to result
6 337 from the BDA structures but the inflow of water from groundwater seep. The year we started
7 338 monitoring the stream reach (2017) was a regional drought, and so we did not observe the spring water
8 339 addition at the place where we installed the triple-BDA configuration. However, 2018 and 2019 were
9 340 considerably wetter years, and we observed groundwater exfiltrating into the stream. We anticipate
10 341 that without the interference of these three external springs, the triple-configuration might have
11 342 lowered stream peaks during rainfall events more than the single- and double-BDA configurations. Our
12 343 findings though indicate that it would be worthwhile for future studies to further test how different
13 344 numbers of BDA installed in sequence cumulatively influence stream flows. Our results also suggest that
14 345 it is important to assess BDA effectiveness along in gaining and losing stream reaches in order to provide
15 346 stream restoration practitioners with clear design guidance.

21 347 5.3 Riparian water table response

22
23 348 BDA installation led to a quick water table rise in the riparian area. Similar to natural beaver dams
24 349 (Westbrook et al., 2006), the water table rise was largest near the stream and tapered off with
25 350 increasing distance from the stream. At 13 m from the stream, there was no significant increase in the
26 351 water table. Our multivariate mixed model indicated that fluctuations in the riparian water table can be
27 352 predicted by the height of stream ponding, at least at the one BDA we studied. The rises in the riparian
28 353 water table we observed post-BDA installation were also found for BDAs installed by Bouwes et al.
29 354 (2016) and Orr et al. (2020), but our values are on average 0.10 m and 0.11 m greater than they
30 355 reported. Our results are not consistent with the observations of Scamardo and Wohl (2020) who noted
31 356 an absence of water table response to BDA installation. However, Scamardo and Wohl cited low
32 357 permeability of floodplain soils as the likely reason, which was not the case in for riparian soils of Pine
33 358 Creek. The conflicting results among studies indicate further research is needed to determine under
34 359 which site conditions BDAs are likely to raise riparian water tables.

35
36 360 Flow reversal was the dominant process to elevate the riparian water table as the amount of water
37 361 ponding in the stream was sufficient to reverse the hydraulic gradient and drive stream water into
38 362 riparian soils, similar to what is observed in places where there are natural beaver dams (Majerova et
39 363 al., 2015; Schmadel, Neilson & Kasahara, 2014). It did not take a very tall BDA structure to cause a flow
40 364 reversal, as the BDAs were built to raise stream stage only to 0.6 m and the ponding was confined
41 365 mostly within the channel. The flow reversal we observed was similar to what occurred in a nearby
42 366 stream when the beaver built small, in-channel dams (Janzen & Westbrook, 2011). Rainstorms elevated
43 367 BDA pond levels, which in turn raised the riparian GW table. Therefore, there is an opportunity to
44 368 investigating the isolated role of rainfall in rising the riparian GW table. The BDA-ponding link to riparian
45 369 GW table under associated predictors of stage and rainfall was confirmed using a 1:1 fit between the
46 370 measured and model-predicted values. Further, the creek we investigated was surrounded by a seasonal
47 371 graminoid marsh wetland characterized by hydric soil which was reported to have relatively uniform and
48 372 as high as hydraulic conductivity of 0.29 m hr^{-1} (He, Vepraskas, Skaggs & Lindbo, 2002; Surridge, Baird &

373 Heathwaite, 2005). Therefore, soil permeability might have augmented the stream-riparian connectivity
374 and consequent flow reversals.

375 Considering that a single BDA, while small, was able to effectively raise the riparian water table within
376 13 m of the stream by changing the hydrologic connectivity of the stream and riparian area, we
377 anticipate that multiple BDAs installed in sequence - with varying numbers and spacings –would expand
378 the portion of the riparian area over which riparian water tables are raised. Future research should
379 explore the dynamics of stream-riparian hydrological connection under various BDA configurations with
380 the goal of identifying whether installing sequences of BDAs compound riparian water table rises so as
381 to provide the evidence with which clear guidelines for BDA use by stream restoration practitioners can
382 be developed.

383

384 6 CONCLUSIONS

385 This study explores the effectiveness of unique BDA configurations in mimicking the ecohydrological
386 functions of natural beaver dams in a degraded spring-fed creek. First, the single-, double- and triple-
387 configurations did not differ in responding to rainfall/events for developing immediate upstream
388 ponding post-installation. Though, deeper, and relatively persistent ponds were developed upstream of
389 the triple-configuration configuration, suggesting that a multi-configuration BDA construct can be more
390 effective than a single-configured BDA. Second, single- and double-configurations partially lowered the
391 downstream stage and discharge by modulating rainfall events and increasing or sustaining the base
392 stage and discharge. The triple-configuration did not perform as expected; downstream stage and flow
393 were elevated rather than reduced, likely due to GW seepage. Results highlight how local hydrological
394 controls when present could have a stronger influence on stream hydrology than BDAs. Third, we found
395 that even the singularly configured BDA we used created sufficient upstream ponding to cause a flow
396 reversal, represented the hydrological function of natural beaver dams on enhancing stream-riparian
397 hydrological connectivity. Our findings reflect that while all BDA configurations used are unlikely to
398 provide 100% similar ecohydrological functions and alike those of natural beaver dams, multiple-
399 configuration BDAs are likely to pond deeper and longer, while the stand-alone BDA we tested likely
400 develop stream-riparian groundwater connectivity in riparian soils of sufficient hydraulic conductivity.
401 We recommend further testing of different BDA configurations – varying heights, widths and spacings –
402 in order to advance the development of guidelines for stream restoration practitioners on BDA
403 installation and use.

404 ACKNOWLEDGEMENTS

405 We thank Greg Lewallen, Amanda Ronnquist, Uswah Aziz, Stephanie Streich and Selena Schut for field
406 assistance, and Greg Shyba and Reg Remple of the Ann and Sandy Cross Conservation Area for logistical
407 support. Field support was provided by the University of Calgary Biogeosciences Institute. Grants from
408 the Natural Sciences and Engineering Research Council of Canada (NSERC) Discovery (RGPIN-2017-

1
2
3 409 05873) and CREATE (463960-2015) programs and the Global Water Futures program supported this
4 410 research.

6
7 411 DATA AVAILABILITY STATEMENT

8
9 412 The data that support the findings of this study are publicly archived in [github] at:
10 413 https://github.com/TariqMunir/Munir-Westbrook-Supplementary-Data_BDAs.git

11
12 414

13
14 415 ORCID

15
16 416 Tariq Munir <https://orcid.org/0000-0002-4591-0978>

17
18 417 Cherie Westbrook <https://orcid.org/0000-0003-1666-3979>

19
20 418

21
22 419

23
24 420

25
26 421

27
28 422

29
30 423

31
32 424

33
34 425

35
36 426

37
38 427

39
40 428

41
42 429

43
44 430

45
46 431

47
48 432

49
50 433

51
52 434

53
54 435

55
56 436

437 REFERENCES

- 438 Bouwes, N., Weber, N., Jordan, C. E., Saunders, W. C., Tattam, I. A., Volk, C., . . . Pollock, M. M. (2016).
439 Ecosystem experiment reveals benefits of natural and simulated beaver dams to a threatened
440 population of steelhead (*Oncorhynchus mykiss*). *Scientific Reports*, 6(28581).
441 doi:10.1038/srep28581
- 442 Briggs, M. A., Lutz, L. K., Hare, D. K., & González-Pinzón, R. (2013). Relating hyporheic fluxes, residence
443 times, and redox-sensitive biogeochemical processes upstream of beaver dams. *Freshwater*
444 *Science*, 32(2), 622-641.
- 445 Butler, D. R., & Malanson, G. P. (2005). The geomorphic influences of beaver dams and failures of beaver
446 dams. *Geomorphology*, 71(1-2), 48-60.
- 447 Charnley, S. (2018). Beavers, landowners, and watershed restoration: experimenting with beaver dam
448 analogues in the Scott River basin, California.
- 449 Dewas, M., Herr, J., Schley, L., Angst, C., Manet, B., Landry, P., & Catusse, M. (2012). Recovery and status
450 of native and introduced beavers *Castor fiber* and *Castor canadensis* in France and neighbouring
451 countries. *Mammal Review*, 42(2), 144-165.
- 452 Dittbrenner, B. J., Pollock, M. M., Schilling, J. W., Olden, J. D., Lawler, J. J., & Torgersen, C. E. (2018).
453 Modeling intrinsic potential for beaver (*Castor canadensis*) habitat to inform restoration and
454 climate change adaptation. *PloS one*, 13(2), e0192538.
- 455 Fairfax, E., & Small, E. E. (2018). Using remote sensing to assess the impact of beaver damming on
456 riparian evapotranspiration in an arid landscape. *Ecohydrology*, 11(7), e1993.
- 457 Feiner, K., & Lowry, C. S. (2015). Simulating the effects of a beaver dam on regional groundwater flow
458 through a wetland. *Journal of Hydrology: Regional Studies*, 4, 675-685.
- 459 Grasby, S. E., Chen, Z., Hamblin, A. P., Wozniak, P. R., & Sweet, A. R. (2008). Regional characterization of
460 the Paskapoo bedrock aquifer system, southern Alberta. *Canadian Journal of Earth Sciences*,
461 45(12), 1501-1516.
- 462 Harvey, J., & Gooseff, M. (2015). River corridor science: Hydrologic exchange and ecological
463 consequences from bedforms to basins. *Water Resources Research*, 51(9), 6893-6922.
- 464 He, X., Vepraskas, M. J., Skaggs, R. W., & Lindbo, D. L. (2002). Adapting a Drainage Model to Simulate
465 Water Table Levels in Coastal Plain Soils. *Soil Science Society of America Journal*, 66(5), 1722-
466 1731. doi:10.2136/sssaj2002.1722
- 467 Hillman, G. R. (1998). Flood wave attenuation by a wetland following a beaver dam failure on a second
468 order boreal stream. *Wetlands*, 18(1), 21-34.
- 469 Janzen, K., & Westbrook, C. J. (2011). Hyporheic flows along a channelled peatland: influence of beaver
470 dams. *Canadian Water Resources Journal/Revue canadienne des ressources hydriques*, 36(4),
471 331-347.

- 1
2
3 472 Johnson, M.F., Thorne, C., Castro, J., Kondolf, M., Rood, S., Mazzacano, C., & Westbrook, C. (2020).
4 473 Biomic river restoration: a new focus for river management. *River Research and Applications*,
5 474 36(1), 3-12.
6
7 475 Karran, D. J., Westbrook, C. J., & Bedard-Haughn, A. (2018). Beaver-mediated water table dynamics in a
8 476 Rocky Mountain fen. *Ecohydrology*, 11(2), e1923.
9
10 477 Landau, S., & Everitt, B. (2004). *A handbook of statistical analyses using SPSS*. Washington, D.C.: CRC.
11
12 478 Lautz, L., Kelleher, C., Vidon, P., Coffman, J., Riginos, C., & Copeland, H. (2019). Restoring stream
13 479 ecosystem function with beaver dam analogues: Let's not make the same mistake twice.
14 480 *Hydrological Processes*, 33(1), 174-177.
15
16 481 Majerova, M., Neilson, B., Schmadel, N., Wheaton, J., & Snow, C. (2015). Impacts of beaver dams on
17 482 hydrologic and temperature regimes in a mountain stream. *Hydrology & Earth System Sciences*
18 483 *Discussions*, 12(1).
19
20 484 Marshall, K. N., Hobbs, N. T., & Cooper, D. J. (2013). Stream hydrology limits recovery of riparian
21 485 ecosystems after wolf reintroduction. *Proceedings of the Royal Society B: Biological Sciences*,
22 486 280(1756), 20122977.
23
24 487 Orr, M. R., Weber, N. P., Noone, W. N., Mooney, M. G., Oakes, T. M., & Broughton, H. M. (2020). Short-
25 488 Term Stream and Riparian Responses to Beaver Dam Analogs on a Low-Gradient Channel
26 489 Lacking Woody Riparian Vegetation. *Northwest Science*, 93(3-4), 171-184.
27
28 490 Persico, L., & Meyer, G. (2013). Natural and historical variability in fluvial processes, beaver activity, and
29 491 climate in the Greater Yellowstone Ecosystem. *Earth Surface Processes and Landforms*, 38(7),
30 492 728-750.
31
32 493 Pilliod, D. S., Rohde, A. T., Charnley, S., Davee, R. R., Dunham, J. B., Gosnell, H., . . . Nash, C. (2018).
33 494 Survey of beaver-related restoration practices in rangeland streams of the western USA.
34 495 *Environmental management*, 61(1), 58-68.
35
36 496 Pollock, M., Wheaton, J., Bouwes, N., & Jordan, C. (2011). Working with beaver to restore salmon
37 497 habitat in the Bridge Creek Intensively Monitored Watershed. *Nation Oceanic and Atmospheric*
38 498 *Administration, Seattle, WA, USA*.
39
40 499 Pollock, M. M., Beechie, T. J., & Jordan, C. E. (2007). Geomorphic changes upstream of beaver dams in
41 500 Bridge Creek, an incised stream channel in the interior Columbia River basin, eastern Oregon.
42 501 *Earth Surface Processes and Landforms*, 32(8), 1174-1185.
43
44 502 Pollock, M. M., Beechie, T. J., Wheaton, J. M., Jordan, C. E., Bouwes, N., Weber, N., & Volk, C. (2014).
45 503 Using beaver dams to restore incised stream ecosystems. *Bioscience*, 64(4), 279-290.
46
47 504 Pollock, M. M., Lewallen, G., Woodruff, K., Jordan, C., & Castro, J. (2018). *The Beaver Restoration*
48 505 *Guidebook: Working with beaver to restore streams, wetlands, and floodplain. Version 2.01*.
49 506 Retrieved from Portland, Oregon. US Fish and Wildlife Service:
50
51
52
53
54
55
56
57
58
59
60

- 1
2
3 507 Polvi, L. E., & Wohl, E. (2012). The beaver meadow complex revisited—the role of beavers in post-glacial
4 508 floodplain development. *Earth Surface Processes and Landforms*, 37(3), 332-346.
5
6 509 Puttock, A., Graham, H. A., Cunliffe, A. M., Elliott, M., & Brazier, R. E. (2017). Eurasian beaver activity
7 510 increases water storage, attenuates flow and mitigates diffuse pollution from intensively-
8 511 managed grasslands. *Science of the total environment*, 576, 430-443.
9
10 512 Rosell, F., Bozser, O., Collen, P., & Parker, H. (2005). Ecological impact of beavers *Castor fiber* and *Castor*
11 513 *canadensis* and their ability to modify ecosystems. *Mammal Review*, 35(3-4), 248-276.
12
13 514 Scamardo, J., & Wohl, E. (2020). Sediment storage and shallow groundwater response to beaver dam
14 515 analogues in the Colorado Front Range, USA. *River Research and Applications*, 36(3), 398-409.
15
16 516 Schmadel, N. M., Neilson, B. T., & Kasahara, T. (2014). Deducing the spatial variability of exchange within
17 517 a longitudinal channel water balance. *Hydrological Processes*, 28(7), 3088-3103.
18
19 518 Silverman, N. L., Allred, B. W., Donnelly, J. P., Chapman, T. B., Maestas, J. D., Wheaton, J. M., . . . Naugle,
20 519 D. E. (2019). Low-tech riparian and wet meadow restoration increases vegetation productivity
21 520 and resilience across semiarid rangelands. *Restoration Ecology*, 27(2), 269-278.
22
23 521 Stout, T., Majerova, M., & Neilson, B. (2017). Impacts of beaver dams on channel hydraulics and
24 522 substrate characteristics in a mountain stream. *Ecohydrology*, 10(1), e1767.
25
26 523 Surridge, B. W., Baird, A. J., & Heathwaite, A. (2005). Evaluating the quality of hydraulic conductivity
27 524 estimates from piezometer slug tests in peat. *Hydrological Processes*, 19(6), 1227-1244.
28 525 doi:10.1002/hyp.5653
29
30 526 Weber, N., Bouwes, N., Pollock, M. M., Volk, C., Wheaton, J. M., Wathen, G., . . . Jordan, C. E. (2017).
31 527 Alteration of stream temperature by natural and artificial beaver dams. *PloS one*, 12(5),
32 528 e0176313. doi:10.1371/journal.pone.0176313
33
34 529 Westbrook, C., Cooper, D., & Butler, D. (2013). Beaver Hydrology and Geomorphology. In J. Shroder, D.
35 530 R. Butler, & C. R. Hupp (Eds.), *Treatise of Geomorphology, Ecogeomorphology* (Vol. 12, pp. 293-
36 531 306). San Diego, CA: Academic Press.
37
38 532 Westbrook, C. J., Cooper, D., & Baker, B. (2011). Beaver assisted river valley formation. *River Research*
39 533 *and Applications*, 27(2), 247-256.
40
41 534 Westbrook, C. J., Cooper, D. J., & Baker, B. W. (2006). Beaver dams and overbank floods influence
42 535 groundwater–surface water interactions of a Rocky Mountain riparian area. *Water Resources*
43 536 *Research*, 42(6). doi:10.1029/2005wr004560
44
45 537 Westbrook, C. J., Ronnquist, A., & Bedard-Haughn, A. (2020). Hydrological functioning of a beaver dam
46 538 sequence and regional dam persistence during an extreme rainstorm. *Hydrological Processes*,
47 539 *n/a(n/a)*. doi:10.1002/hyp.13828
48
49 540 White, R. (2016). Beaver Reintroduction Project. *CTV News*. Retrieved from
50 541 [https://calgary.ctvnews.ca/beaver-pair-reintroduced-into-the-wild-after-developing-fondness-](https://calgary.ctvnews.ca/beaver-pair-reintroduced-into-the-wild-after-developing-fondness-during-rehabilitation-1.3936537)
51 542 [during-rehabilitation-1.3936537](https://calgary.ctvnews.ca/beaver-pair-reintroduced-into-the-wild-after-developing-fondness-during-rehabilitation-1.3936537)
52
53
54
55
56
57
58
59
60

1
2
3 543 [dataset] Munir, T. M., & Westbrook, C. J; (2020); TariqMunir / Munir-Westbrook-Supplementary-
4 544 Data_BDAs; github; https://github.com/TariqMunir/Munir-Westbrook-Supplementary-Data_BDAs

5
6 545

7
8 546

9
10 547

11
12 548

13
14 549

15
16 550

17
18 551

19
20 552

21
22 553

23
24 554

25
26 555

27
28 556

29
30 557

31
32 558

33
34 559

35
36 560

37
38 561

39
40 562

41
42 563

43
44 564

45
46 565

47
48 566

49
50 567

51
52 568

53
54 569

55
56 570

57

58

59

60

For Peer Review

1
2
3 571
4
5 572
6
7 573
8
9 574
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33 575
34
35 576
36
37 577
38
39 578
40
41 579
42
43 580
44
45 581
46
47 582
48
49 583
50
51 584
52
53 585
54
55 586
56
57
58
59
60

TABLES AND FIGURES WITH CAPTIONS

Table 1. Statistical analysis results of a linear mixed-effects model with fixed effects of BDA configuration (single, double, triple) and rainfall, random effects of BDA configuration (distance from top of the reach), and an outcome variable of BDA pond water level.

Effect / terms	BDA configuration pond water level (m)			
	df	F	p	LogWorth (-log ₁₀ (p))*
BDA configuration (overall model)	2, 583	15.99	<0.001	12.31
single-configuration	1, 96	7.18	0.009	3.23
triple-configuration	2, 290	19.03	<0.001	8.72
double-configuration	1, 193	22.09	<0.001	8.80
(triple-configuration – double-configuration)	-	2.74	0.006	-
(double-configuration – single-configuration)	-	5.24	<0.001	-
Rainfall	1, 583	4.05	0.045	1.35
BDA config. × rainfall	2, 583	1.25	0.047	1.21

* A LogWorth value of >2.0 shows significance at 0.01 level ((-log₁₀(0.01) = 2). Bold p values show p<0.05.

Table 2. Statistical analyses results of 1) paired t-tests between pre- and post-BDA treatment stream stage and discharge, and 2) a linear mixed-effects model with fixed effects of BDA configuration (single, double, triple), pond level (BDA-1 – BDA-6) and rainfall measured over 2018-2019, random effects of BDA configuration (distance from top of the reach) and the outcome variables of stream stage and streamflow*.

Effect/term	Stream stage (m)			Streamflow (l/s)		
	df	F or t-ratio	p/LogWorth (-log ₁₀ (p))	df	F or t-ratio	p/LogWorth (-log ₁₀ (p))
PAIRED t-TEST (Pre- vs post-BDA)						
1-config. (2018 SG4 – SG3) vs (2019 SG4 – SG3)	1, 55	1.40	0.043	1, 55	1.7	0.049
3-config. (2018 SG3 – SG2) vs (2019 SG3 – SG2)	1, 55	4.38	<0.001	1, 55	-0.21	0.834
2-config. (2018 SG2 – SG1) vs (2019 SG2 – SG1)	1, 55	2.30	0.025	1, 55	0.17	0.863
LINEAR MIXED-EFFECTS MODEL						
BDA configuration	2, 285	98.20	<0.001/ 32.44	2, 285	206.2	<0.001/ 55.38
Tukey: 1-config. (stage/flow = 0.060/2.40) vs 3-config. (stage/flow = 0.08/9.74)	2, 285	5.62	<0.001	2, 285	9.08	<0.001
Tukey: 1-config. vs 2-config. (stage/flow = 0.065/1.75)	1, 285	-7.79	<0.001	1, 285	-10.41	<0.001
Tukey: 3-config. vs 2-config.	2, 285	13.87	<0.001	2, 285	20.22	<0.001
Rainfall	1, 285	1.10	0.296	1, 285	1.83	0.177
BDA pond level	4, 285	1.15	0.251	2, 285	1.67	0.197
BDA config. × BDA pond level	2, 285	166.37	<0.001/ 47.88	2, 285	109.26	<0.001/ 35.22
BDA (1-config.) × BDA pond level (0.4233m) × rainfall (2.28mm)	2, 285	2.16	0.032/ 1.50	2, 285	2.82	0.005/ 4.62

* pre- and post-treatment periods are late June 2017 to early August 2018, and early August 2018 to early August 2019, respectively. Stage or flow value used was a difference between above and below a configuration. A LogWorth value of >2.0 signifies 0.01 level ((-log₁₀(0.01) = 2) and provides strength of significance with greater the value more the strength. Bold p values show significance at 0.05 or 0.01 level.

587
588
589
590
591
592
593
594
595

Table 3. Statistical results of 1) a paired t-test between pre- and post-BDA treatment groundwater table, and 2) a mixed-effects model with fixed effects of BDA-6 pond water level, rainfall and stage, and random effect of groundwater well location, and an outcome variable of riparian groundwater table *.

Effect / term	Riparian groundwater table wells						
	1 (2 m south)			2 (5 m south)		3 (13 m south)	
	df (n=131)	F/t ratio	p (% effect)	t- ratio	p	F/t ratio	p (% effect)
PAIRED t-TEST (pre- vs post-BDA)	-	37.95	<0.001	3.62	<0.001	-1.07	0.285
Linear mixed-effects model							
BDA-6 mean water level (0.3472 m)	1, 72	106.9	<0.001			1.14	0.290
		3	(73%)				
Rainfall (2.44mm)	1, 72	6.45	0.027	Well-2 was not		5.34	0.003
			(10%)	monitored during 2019			(17%)
Stage (0.0674m)	1, 72	3.74	0.045	due to malfunction of		51.41	<0.001
				the level logger;			(78%)
BDA pond water level × rainfall	1, 72	1.54	0.009	therefore, not included		4.40	0.040
				in LMEM			
Rainfall × stage	1, 72	1.59	0.211			3.91	0.052
BDA pond water level × stage × rainfall	1, 72	2.21	0.142			3.44	0.068

* depth to GW table. Pre- and post-treatment periods are late June 2017-early August 2018, and early August 2018-early August 2019, respectively. For linear mixed-effects model, only 2019 data is used since pond water level was available for 2019 only. Stage measurements are from SG-4.

596

597

598

599

600

601

602

603

604

605

606

607

608

609

Fig. 1. Location of study stream equipped with beaver dam analogue (BDA)/configurations, pond gauges (PG), stream gauges (SG) and groundwater (GW) monitoring wells at Ann & Sandy Cross Conservation Area near Calgary in Alberta, Canada. Six BDAs (BDA-6 to BDA-1) from upstream to downstream are shown by red bars along ~1075 m long reach. 1, 2 and 3 red bars represent single-, double-, and triple-configurations, respectively. A group of same configurations is called a series. Each BDA is instrumented with an upstream PG (PG-6 to PG-1). Four SGs (SG-4 to SG-1, shown by cross signs) before and after each of the three configuration/series were installed to monitor stream stage and discharge. A 13 m long transect, south of BDA-6 was installed with three shallow GW monitoring wells at ~2, 5 and 13 m distances (shown by black spheres). One surface spring fed the creek (teal-blue line) and three groundwater springs merged with the creek (black arrows). Instrumentations may not be up to the scale.

Fig. 2. Beaver dam analogue (BDA) water level elevations measured after BDA installation in August 2018, and BDA failure in August 2019 (A). Mean daily BDA pond water levels (B), averaged over three BDA configurations (single-, double- and triple-configuration) series (C).

Fig. 3. Mean daily stream stage upstream and downstream of: single-configuration BDA-6, with a hyetograph on top x-axis and right y-axis (A), triple-configuration series (B), double-configuration series (C). Overall stage upstream and downstream of study reach (D). The hyetograph is applicable for all four figure panels.

Fig. 4. Mean daily streamflow upstream and downstream of: single-configuration BDA-6, with a hyetograph on top x-axis and right y-axis (A), triple-configuration series (B), double-configuration series (C). Overall streamflow upstream and downstream of study reach (D). The hyetograph is applicable for all four figure panels.

Fig. 5. Observed peak discharge relationship between above (x-axis) and below (y-axis) a BDA configuration/series is shown by plotting all storm events ($n = 19$) extracted from a continuous time series of streamflow logged during August 2018 and August 2019. Relationships between discharges at upstream and downstream of: single-configuration BDA (A), triple-configuration series (B), and double-configuration series (C) are drawn. Overall peak discharge upstream and downstream of reach is shown by D. Likewise, observed total event discharge relationships are also shown. Relationships between total event discharges at upstream and downstream of: single-configuration BDA-6 (E), triple-configuration series (F), and double-configuration series (G) are shown. Overall total event discharge upstream and downstream of reach is shown by H.

Fig. 6. Mean daily rainfall (bars), and riparian groundwater levels (lines) at three monitoring wells during May-Oct of 2017-2019 (A). The wells were 1.25 m deep from soil surface and ~2, 7 and 13 m south of BDA-6 (single-configuration). The GW levels at well-2 are missing in 2019 due to levellogger's malfunction. Negative values indicate belowground water level. Hydraulic gradients pre- and post-installation of BDA (6) are shown during study years (B). Overall, pre-BDA installation hydraulic gradient

1
2
3 646 indicates flow from the riparian area to the stream. Post BDA installation hydraulic gradient shows flow
4 647 reversal from stream toward riparian area.
5

6 648 Fig. 7. Impacts of stream stage (A) and a single-configuration BDA-6 pond water level (B) on riparian
7 649 water levels at well-1 and well-3 during 2019. Goodness of fit (R^2) between modelled and observed
8 650 riparian groundwater table at well-1 (C) and well-3 (D).
9

10
11 651

12
13 652

14
15 653

16
17 654

18
19 655

20
21 656

22
23 657

24
25 658

26
27 659

28
29 660

30
31 661

32
33 662

34
35 663

36
37 664

38
39 665

40
41 666

42
43 667

44
45 668

46
47 669

48
49 670


50
51 671

52
53 672

54
55 673

56
57 674


675
676



677
678
679
680
681
682
683

Fig. 1


684
685
686
687



688
689
690
691
692

Fig. 2


Peer Review



693

694

695 Fig. 3




696

697

698

699 Fig. 4



700

701

702

703 Fig. 5





Fig. 6

view

716



717

718 Fig. 7

719